



10/533268



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

**PRIORITY
DOCUMENT**
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

EPO - DG1

02 DEC 2003

112

REC'D 23 DEC 2003

WIPO


PCT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed

Dated

R. Mahoney
20 November 2002

BEST AVAILABLE COPY --

Patents Form 1/77

Patents Act 1977
(Rule 16)

The
Patent
Office

Fee - £145

04NOV02 E760544-11 002094
P01/7700 0.00-0225567.7

Request for grant of a patent



1/77

The Patent Office

Cardiff Road
Newport
Gwent NP9 1RH

1. Your reference 03 41959

2. Patent application number 0225567.7

01 NOV 2002

3. Full name, address and post code of the or each applicant
Nokia Corporation
Keilalahdentie 4
02150 Espoo
Finland

Patents ADP number

If the applicant is a corporate body, give the country/state of its incorporation

FI

765227003

4. Title of the invention HYBRID NETWORKS

5. Name of your agent VENNER, SHIPLEY & CO

"Address for service" in the United Kingdom to which all correspondence should be sent

20 LITTLE BRITAIN
LONDON
EC1A 7DH

Patents ADP

1669004

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or each of these earlier applications and the or each application number

Country	Priority application number	Date of filing

7. If this application is divided or otherwise derived from an earlier UK application, give the number and filing date of the earlier application

Number of earlier application	Date of Filing

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'YES' if:
a) any applicant in 3: above is not an inventor, or
b) there is an inventor who is not named as an applicant, or
c) any named applicant is a corporate body)

YES

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description 19

Claim(s) 6

Abstract 1

Drawing(s) 8 *as*

10. If you are also filing any of the following state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (*Patents Form 7/77*)

Request for preliminary examination and search (*Patents Form 9/77*) One /

Request for substantive examination (*Patents Form 10/77*)

Any other documents

11.

I/We request the grant of a patent on the basis of this application.

Signature

Date

Verner Shipley & Co.

1 November 2002

12. Name and daytime telephone number of person to contact in the United Kingdom

PAUL DERRY
020 7600 4212

Hybrid Networks

The present invention relates to a hybrid network. The invention relates also to a content delivery method, to an agent connectable to a network, and to a content delivery system.

As a result of the perceived needs of the consumer, it is considered that the opportunities offered by digital technology will result in a convergence of product features and capabilities. Such a convergence is already evident today in the provision of add-on and even integrated cellular telephony capabilities to the so-call personal data assistant (PDA) product category. Such convergence will undoubtedly bring advantages to the consumer in that she will no longer need to transport a range of devices with her.

However, from the perspective of the manufacturer and/or service provider, the convergence of products brings particular challenges. In the case of the manufacturer, such challenges include the need to integrate the functionality of what previously were devices having different operating systems, power requirements and such like, and typically all within a smaller, more compact form factor. For the service provider, the challenge is to provide existing and new services in a form which complements the synergies brought to the user by the convergence of functionality in the product.

According to a first aspect of the invention, there is provided a content delivery method comprising establishing a set of user preferences related to delivery of content, sourcing content in response to a request received from a terminal connected to a network and selecting based on said set of user preferences a network over which to deliver said content to said terminal.

This method can allow content to be delivered over a network which is most suitable to the user, providing flexibility of service. Allowing user preferences to be settable and to be acted on can allow a user to feel in control of content delivery services, which might cause the user to demand more content than otherwise. Content delivery services using the method could be considered as customisable, and thus user-considerate. Also, if the

user preferences are changeable, in response to changed service conditions or otherwise, the invention may allow a user confidence to subscribe to or merely request content which otherwise would have been missed, enriching user experience. The user preferences might relate to cost and/or delivery timing preferences.

5

The method preferably comprises maintaining in an agent a log of sourced content relating to the request, which could include an indication of the delivery status of the content. Such could allow a network straightforward management of content relating to the user, and avoid the user or the user's terminal having to ensure that all requested content has been delivered, and delivered fully and correctly.

10

Preferably, the method includes acknowledging receipt of the content over a or the duplex network, which allows the preferred feature of updating the delivery status of the log on receiving an acknowledgement receipt.

15

In a preferred example, the method comprises notifying over a duplex network the terminal prior to the delivery of content over a simplex network. This is particularly advantageous since the enabling of a receiver for reception of content over a simplex network can consume power at relatively high rates, especially where the simplex network is a DVB network or similar. Power consumption minimisation is particularly important in mobile terminals.

20

The content may be selected by reviewing content items on a data carousel, and determining from the reviewing step if any forthcoming content matches the user request, or by conducting a search for content relating to the request, preferably using the internet. Searching for content on the internet is expected to be particularly prevalent in years to come. Using the invention, it may be possible to provide content relating to any given subject through regular searches, without the user having to instruct the search on each occasion.

25

30

To aid searching, the method may include comprising storing in an agent information relating to the last update of content relating to the request, and/or information relating

to the user's time and/or frequency of updating preferences, and/or information relating to domains to which searching relating to the content request is limited.

5 According to a second aspect of the invention, there is provided an agent connectable to a network, the agent being operable to establish a set of user preferences relating to delivery of content to a user terminal, to source content in response to a user request, and to deliver said content to a user terminal over a network selected in dependence on said set of user preferences.

10 The agent preferably is arranged to maintain a log of sourced content relating to the request, which preferably includes an indication of the delivery status of the content. Advantageously, the agent is arranged to update the delivery status of the log on receiving an acknowledgement receipt.

15 The user preferences could relate to cost and/or delivery timing preferences.

The agent may comprise means for reviewing content items on a data carousel, and means for determining from the reviewing step if any forthcoming content matches the user request.

20

If the agent includes means for searching for content relating to the request, it also preferably includes means for storing information relating to the last update of content relating to the request, and/or means for storing information relating to the user's time and/or frequency of updating preferences, and/or means for storing information relating to domains to which searching relating to the content request is limited.

25

In accordance with a third aspect of the invention, there is provided a content delivery system comprising a first duplex network, a second network and a user terminal connectable to said first and second networks, wherein the system further comprises an agent connectable to said first and second networks, the agent being operable to source content in response to a user request received from said user terminal via said first

30

network, and to deliver said content to said terminal over a network selected in accordance with a set of user preferences.

User preferences could be established by the agent, or be generated by the terminal.

5

The second network could be a simplex network, such as a broadcast network, for example a DVB network. In such a case, it is particularly advantageous for the system to include means for notifying over the first network the terminal prior to the delivery of content over the second network. Instead of a simplex network, though, the second
10 network could be a duplex network such as a Bluetooth network, or a network operating to any of the GPRS, GSM, 3G or WLAN standards.

The agent might be arranged to maintain a log of sourced content relating to the request, and to maintain in the log an indication of the delivery status of the content.

15

If the terminal is arranged to acknowledge receipt of the content over the duplex network or one of the duplex networks, the agent preferably is arranged to update the delivery status in the log on receiving an acknowledgement receipt.

20 The user preferences could relate to cost and/or delivery timing preferences.

The system may comprise means for reviewing content items on a data carousel, and means for determining from the reviewing step if any forthcoming content matches the user request. Alternatively or in addition, the system could comprise means for
25 conducting a search for content relating to the request, preferably using the internet. In either case, the agent preferably is arranged to store information relating to the last update of content relating to the request, and/or information relating to the user's time and/or frequency of updating preferences, and/or information relating to domains to which searching relating to the content request is limited.

30

Embodiments of the invention will be described, by way of example only, with reference to the accompanying drawings, in which:

Figures 1a, 1b and 7 are diagrams illustrative of hybrid systems in accordance with one aspect of the present invention and including agents according to another aspect of the invention;

5 Figure 2 is a schematic diagram of a mobile telephone and its user interface components; Figure 3 is a schematic diagram illustrating operation of the Figure 2 telephone;

Figure 4 is a schematic diagram of an agent according to one aspect of the invention and included in another aspect of the invention;

Figures 5a, 5b and 6 are flowcharts illustrating operation of the Figures 1a and 1b
10 systems; and

Figure 8 is a schematic diagram of a preferred form of agent.

In the Figures, like reference numerals are used to refer to like elements throughout.

15 With reference to Figures 1a and 1b, there is shown a hybrid network 1 connectable to a source of content 3 on an intranet and/or the Internet. The hybrid network 1 includes a plurality of user-operated terminals 5, both mobile and fixed, a first duplex communication network 7, and in the case of Figure 1a a second simplex broadband network 9 and in the case of Figure 1b, a so-called 'hot-spot' 11 providing an access
20 point to the source of content 3 using a wireless local area network including, but not limited to, a low power radio frequency network. Clearly, the hybrid network 1 can also comprise a combination of the above two examples in which both the second simplex broadband network 9 and at least one hot-spot 11 are available in conjunction with the first duplex network 7.

25

Figure 2 illustrates the main components relied upon by a user in interacting with a terminal 5. Thus, the terminal 5 includes a keypad 15, a microphone 17, a loudspeaker 19 and a display 21. The operation of these components is under the control of a controller 23 shown in more detail in Figure 3. The controller 23 performs not only the tasks
30 necessary to provide interaction with the user via the above described elements, but also ensures that the terminal 5 operates correctly within the hybrid network 7. Thus, the controller 23 is connected to a memory 25 for storage of instructions relevant to the

operation of the terminal. User data is stored on long term storage 27 such as flash media and the like, again the task of providing access to such data is carried by the controller 23. A transceiver section 29 connected to a bus 31 serving the controller 23 interprets radio frequency and/or infrared signals arriving at the terminal 5 and similarly
5 converts output from the controller 23 into the appropriate radio frequency and/or infrared signals. The particular format of the signals received and transmitted by the terminal 5 is determined by the network portion 7, 11, 9 of the hybrid network with which the terminal is communicating. Thus, where the terminal 5 is in communication with the first duplex network 7, then the appropriate configuration of the transceiver
10 section 29 is selected by the controller 23. Similarly, the transceiver section 29 is configured to match the requirements of the simplex network 9 or hot-spot 11 as appropriate.

Turning now to Figure 4, there is shown an agent 33 resident on a network element,
15 which in this case is a server 13 (see Figure 1a and Figure 1b) under the control of the operator. The agent 33 can be a software application running on the server 13, although the agent may alternatively be provided in hardware or as a combination of software and hardware. Furthermore, the agent 33 may comprise a number of processes hereinafter referred to as modules each resident on one or more different distributed network
20 elements.

The agent 33 has a communication module 35 which facilitates communication with external processes linked to it via a network connection 37 through the transmission and reception of data packets corresponding to a particular IP protocol, such as IPv6. The
25 communication module 35 is arranged to determine those packets which are intended for delivery to the agent 33, and these packets are passed to a control module 39.

The control module 39 carries out the core processes of the agent 33 and as such has access to a log module 41 which module retains details of terminal 5 sessions, namely a
30 list of activity which has taken place with respect to a particular terminal 5. The log module 41 further provides the controller with a mechanism for maintaining an indication of currently active sessions that are taking place with terminals. As terminals 5

enter into communication with the agent 33, respective entries are made in the log module 41 in accordance with instructions received from the control module 39. As has been mentioned, the log module 41 records any activity that takes place during a terminal session.

5

The control module 39 is further provided with access to a user preference module 43. This module 43 may be located on the server 13 in the sense that communication with the module 43 takes place directly between the control module 39 and the user preference module 43 or it may be distributed in the sense that communication with the user preference module 43 is made via the communication module 35 and network connection 37. Indeed, it may be that the log module is also distributed over the network. The user preference module 43 comprises a store of information relating to the individual preferences of a particular terminal, or a group of terminals such as those belonging to a particular entity (a company or an individual). The preferences provided by a user may include a definition of the cost and delivery timescale the user attaches to the receipt of particular content. As is described in more detail below, the agent 33 is provided with details of the particular content or service (these terms being used interchangeably throughout the specification) to be delivered to the user through a request generated either at the terminal or through a separate web-based interface, for example. The request may be generated in real-time in the sense that the agent 33 responds to the request during an interactive session exhibiting a low level of latency, or the request may be generated and then acted upon by the agent 33 at a later time, such as where resolution of the request is contingent upon a factor such a particular delivery method being available.

25

In the present embodiment, the communication between the terminal 5, the agent 33 and content provider is carried out utilising the IPv6 protocol, although this should not be understood to limit the invention to use of this particular protocol since any suitable protocol, such as IPv4 for example, could be used.

30

Referring again to Figure 1a and Figure 1b, the first duplex communication network 7 is a cellular telephony network operating in accordance with one of many well-understood

standards such as GSM, GPRS, CDMA, WCDMA and the like. All such cellular telephony networks share the characteristic of serving a plurality of mobile terminals from a fixed network of base stations operated by a telecommunication network operator, hereinafter termed a network operator. The network operator may also provide
5 services as a service provider, although the provision of services to terminal users may be carried out by service providers who need not themselves be responsible for provision of the network services. A further characteristic shared by such networks is that each utilises a specific air interface and transmission technique. Thus, the transceiver section
29 of the terminal 5 is adapted to suit a particular air interface and transmission
10 technique. In some terminals, there may exist the capability to have a plurality of transceiver configurations within one transceiver, rather than a plurality of transceivers within the transceiver section 29, such as is found in so-called software radios.

With respect to Figure 1a, as has been mentioned above, the second simplex network 11
15 is provided by a simplex or unidirectional broadband network such as a terrestrial Digital Video Broadcast DVB-T network. The second simplex network 11 includes a data carousel 45 which is operated by a service provider who may also be the network operator. The data carousel 45 is a form of repository into which services are placed and from which these services are selected for delivery over the second network 11 to one or
20 more terminals 5. In other words, the data carousel 45 comprises a number of files each corresponding to a service and these files are broadcast on a cyclical basis. The data carousel 45 has sufficient capacity to store a large number of services. Typically, the services will include content obtained from a content source 3.

25 In addition to the second network, Figure 1a also shows the operator server 13 which forms part of the first duplex network 7. The operator server 13 also hosts the agent 33 and the agent 33 is capable of connecting via the communication module 35 to service providers via the Internet and also to the data carousel 45.

30 With respect to Figure 1b, the second network is, as has already been indicated, a wireless LAN or LPRF hot-spot 9. As in the case of Figure 1a, the operator server 13 forms part of the first duplex network 7. The operator server 13 also hosts the agent 33. The agent

33 is capable of connecting via the communication module 35 to service providers via the Internet and to the hot-spot 11.

To understand the invention more completely, reference is made to the flowcharts of Figure 5 and Figure 6, in relation to the examples shown in Figures 1a and 1b respectively.

Firstly with reference to Figure 5, in which a user enters a subscription for a particular service such as a top ten MP3 download list, which is updated on a once-per-week basis.

10

Initially, the user enters a subscription request at step 100 via a keyboard 15 input, the controller 39 interprets the input and the request is appropriately formatted before being delivered via the first duplex network 7 to the user preference module 43 where the subscription request is held at step 101. The subscription request may additionally incorporate delivery parameters which the agent 33 should comply with when meeting the subscription request, the parameters being such as cost, time of delivery and the like.

Subsequently, at step 102, the control module 39 instructs the communication module 35 to select and then deliver packets of data identifying the forthcoming content of the data carousel 45 of the second simplex network 9 to the control module 39 for analysis. This is carried out on a periodic basis. On receipt of such packets, the control module 39 checks the preference module 43 to determine what subscription requests have been received. If the control module 39 determines at step 103 that a user subscription request held by the user preference module 43 identifies content forthcoming on the data carousel 45, the control module 39 proceeds at 104 to the next step 105, otherwise the control module 39 continues the process 102 of analysing packets of data identifying the forthcoming content of the data carousel 45.

Where content has been identified as forthcoming and of interest to a user, the control module 39 proceeds as follows. The control module 39 raises a query at step 105 with the log module 41 in order to determine the status of content delivery made to a terminal 5 of the user. In particular, the control module 39 attempts to determine from the log

module 41 whether the specific content forthcoming on the data carousel 45 has previously been successfully delivered to the terminal 5. If the result of the query is negative in the sense that there is no log entry indicative of the content having been delivered, the control module 39 proceeds at 106 to step 107. Then, the control module
5 39 extracts, from the data identifying the forthcoming content, details of the transmission time and channel. These details are then passed to the communication channel in the form of a request 107 which is then delivered over the first duplex network 7 to the terminal 5 of the user.

10 The request is received by the transceiver section 29 of the terminal 5 and passed to the controller 23 where it is analysed such that the controller 23 recognises that a delivery of content over the second simplex network 9 is imminent. Consequently, the controller 23 ensures that the transceiver section 29 is reconfigured to receive the content over the second simplex network 9 at the previously informed delivery time. As a result, the
15 terminal 5 is able to receive the desired content via the appropriately configured transceiver section 29 into storage 25 whereupon it may be consumed by the user in accordance with the distribution policies of the content provider. As a final step, once delivery of the content has occurred, the controller 23 sends a delivery acknowledgement message via the appropriately configured transceiver section 29 over the first duplex
20 network 7, which message is addressed to the agent 33.

The acknowledgement message is accepted by the communication module 35 and passed to the control module 39 of the agent 33. The control module 39 ensures that the log
25 module 41 is updated with a flag indicating successful delivery of the particular content.

In another example based on the same user preferences, the user enters a subscription request at step 200 via a keyboard 15 input, input is interpreted by the controller 23 and the request is appropriately formatted before being delivered via the first duplex network to the agent 33 and finally to the user preference module 43 where the subscription
30 request is held. The subscription request may additionally incorporate delivery parameters which the agent 33 should comply with when meeting the subscription request such as cost, time of delivery and the like.

With reference both to Figure 1b and Figure 5b, the terminal is subsequently carried by the user into a hot-spot 11 provided by a Wireless Local Area Network WLAN, although similar functionality could be provided by a Low Power Radio Frequency hot-spot such as one provided by a Bluetooth transceiver. On entry to the hot-spot 11 at step 201, the terminal controller 23 is notified by the transceiver section 29 that the terminal 5 is now within the hot-spot 11. The controller 23 thereupon generates a notification announcement for delivery at step 202 to the agent 33. The notification announcement contains data indicative of the presence of the terminal 5 in the particular hot-spot 11. The announcement is sent via the appropriately configured transceiver section 29 over the second duplex network provided by the hot-spot 11 and ultimately is detected by the communication module 35 of the agent 33 and passed to the control module 39. The control module 39 thereupon determines that a user subscription request is being held by the user preference module 43 which request identifies specific content. The control module 39 then at step 203 raises a query with the log module 41 in order to determine the status of content delivery made to a terminal of the user. In particular, the control module 39 attempts to determine from the log module 41 whether the specific content has previously been successfully delivered to the terminal 5. If the result of the query is negative in the sense that there is no log entry indicative of the content having been delivered, the control module 39 proceeds at step 204 to the next step 205 which is to attempt to source the content from a content provider. Thus, the control module 39 either generates a search query using an appropriate search engine, which may be restricted to collections of content held by a particular content provider, to obtain a link to the content, or the source of the content is predefined in the sense that the user preferences provide an explicit link to the desired content. In either case, the control module 39 then downloads the content from the particular location 3 and forwards at step 205 the content over the second duplex network or hot-spot 11 to the terminal 5 whereupon it may be consumed by the user in a manner appropriate to the distribution conditions imposed by the content provider. As a final step, once delivery of the content has occurred, the controller 23 sends a delivery acknowledgement message via the appropriately configured transceiver section 29 over the second duplex network 11, which message is addressed to the agent 33.

The acknowledgement message is accepted by the communication module 35 and it is passed to the control module 39 of the agent 33. The control module 39 ensures at step 206 that the log module 41 is updated with a flag indicating successful delivery of the particular content.

In still another example, the user generates, using her terminal 5, an immediate request 300 for content in accordance with a possibly predefined set of preferences which include setting a maximum transport cost for the desired content of €n and a best efforts for minimum delivery latency subject to the overriding transport cost constraint. As described above, the user will have previously entered her subscription preferences request via a keyboard 15 input in which the controller 23 interprets the input and the request is appropriately formatted before being delivered via the first duplex network 7 to the user preference module 43 where the subscription request is held. The subscription request incorporates the aforementioned delivery parameters which the agent 33 must comply with when meeting the subscription request.

With particular reference again to Figure 1b and Figure 6, having received the immediate request for content the controller 23 determines at step 301 whether the terminal 5 is presently located in a hot-spot 11. If this is the case, the request is sent at step 302 via the appropriately configured transceiver section 29 over the second duplex network provided by the hot-spot 11 and ultimately is detected by the communication module 35 of the agent 33 and passed to the control module. The control module 39 thereupon determines that a user subscription request is being held by the user preference module 43, which request identifies specific content. Assuming the cost constraint is not broken by the intended delivery using the second duplex network 11, the control module 39 then proceeds to the next step in the process which is to attempt to source the content from a content provider. Thus, the control module 39 either generates a search query using an appropriate search engine which may be restricted to collections of content held by a particular content provider, in order to obtain a link to the content, or the source of the content is predefined in the sense that the user preferences provide an explicit link to the desired content. In either case, the control module 39 then downloads the content 13

from the particular location and forwards the content over the second duplex network 11 to the terminal 5 whereupon it may be consumed by the user in a manner appropriate to the distribution conditions imposed by the content provider. As a final step, once delivery of the content 3 has occurred, the controller 23 sends a delivery
 5 acknowledgement message via the appropriately configured transceiver section 29 over the second duplex network 11, which message is addressed to the agent 33.

However, where the terminal 5 is not located within a hot-spot 11 or the cost of delivery via the second hot-spot duplex network 11 exceeds €n, the controller 23 sends at 303 the
 10 request via the first duplex network 7 utilising the appropriately configured transceiver section 29. The request is received in the communications module 35 and passed to the control module 39 where the agent 33 seeks a delivery cost estimate from the first duplex network 7. Where the cost does not exceed €n then the control module 39 proceeds by attempting to source the content from a content provider. Thus, the control module 39
 15 either generates a search query using an appropriate search engine, which may be restricted to collections of content held by a particular content provider, in order to obtain a link to the content, or the source of the content is predefined in the sense that the user preferences provide an explicit link to the desired content. In either case, the control module 39 then downloads the content 3 from the particular location and
 20 forwards 304 the content 3 over the first duplex network 7 to the terminal 5 whereupon it may be consumed by the user in a manner appropriate to the distribution conditions imposed by the content provider. As a final step, once delivery of the content 3 has occurred, the controller 23 sends a delivery acknowledgement message via the
 25 appropriately configured transceiver section 29 over the first duplex network 7, which message is addressed to the agent 33.

In the event that immediate delivery is not possible over the first duplex network 7 because of the cost constraint, then the control module 29 generates a confirmation request for delivery 305 to the terminal 5 which when received over the first duplex
 30 network 7 by the transceiver section 29 is passed to the controller 23 and suitably formatted for presentation on the display 21 of the terminal 5, whereupon the user can elect whether to override the cost constraint and request immediate delivery 306 or

alternatively to confirm that the cost constraint should not be broken 307. In the former case 306, delivery 308 proceeds at a cost exceeding the constraint in the manner mentioned above, namely the control module 39 proceeds by attempting to source the content from a content provider. Thus, the control module 39 either generates a search
5 query using an appropriate search engine, which may be restricted to collections of content held by a particular content provider, in order to obtain a link to the content, or the source of the content is predefined in the sense that the user preferences provide an explicit link to the desired content. In either case, the control module 39 then downloads the content 3 from the particular location and forwards the content over the first duplex
10 network 7 to the terminal 5 whereupon it may be consumed by the user in a manner appropriate to the distribution conditions imposed by the content provider. As a final step, once delivery of the content 3 has occurred, the controller 23 sends a delivery acknowledgement message via the appropriately configured transceiver section 29 over the first duplex network 7, which message is addressed to the agent 33.

15 In the case where confirmation 307 is received from the terminal 5 that the delivery cost constraint is not to be exceeded, the control module 39 proceeds by attempting to source the content from a content provider. Thus, the control module either generates a search query using an appropriate search engine, which may be restricted to collections of
20 content held by a particular content provider, in order to obtain a link to the content, or the source of the content is predefined in the sense that the user preferences provide an explicit link to the desired content 3. This link to the desired content 3 is then logged 309 in the log module 41 and flagged as being an outstanding request to deliver content 3 to the terminal 5. Subsequently, when the terminal 5 enters a hot-spot 11 a notification
25 announcement is generated at step 310 by the terminal 5. As previously described, the announcement is sent via the appropriately configured transceiver section 29 over the second duplex network provided by the hot-spot 11 and ultimately is detected by the communication module 35 of the agent 33 and passed to the control module 39. The control module 39 then raises a query with the log module 41 in order to determine the
30 status of content delivery made to a terminal 5 of the user. In particular, the control module 39 attempts to determine from the log module 41 whether the specific content has previously been successfully delivered to the terminal 5. In this case, the control

module 39 also determines that there is an outstanding delivery request for the specific content 3 and using the link provided by the log module 41, the agent 33 downloads the specific content 3 and forwards 311 the content 3 over the first duplex network 7 to the terminal whereupon it may be consumed by the user in a manner appropriate to the distribution conditions imposed by the content provider. As a final step, once delivery of the content 3 has occurred, the controller 23 sends a delivery acknowledgement message via the appropriately configured transceiver section 29 over the first duplex network 7, which message is addressed to the agent 33. On receipt of the acknowledgement message, the control module 39 is able to instruct the log module 41 to update 312 the log and to change the flag state to indicate successful delivery of the content 3.

A further embodiment of the invention is now described with reference to Figures 7 and 8. Referring firstly to Figure 7, a system 50 is based on the system of Figure 1a, the description of which is not reproduced here for the sake of conciseness. The main differences are in the provision of plural agents 3, 3a, 3b, which are associated with the operator server 13 and the internet, and in the data carousel 45 being included within a broadcast operator server 51. A content cache 52 is connected to the broadcast operator server 51 to allow communication therebetween. Content servers 53, 54 and 55 are connected for interaction with the internet.

20

The agent 3 is shown in more detail in Figure 8. The agent 3 includes a user preference database 60, a last update database 61, an update frequency database 62, a content domain database 63 and an agent content cache 64. The information shown in the databases 60 to 63 relate to a single user or group of users. Operation is as follows. A user of the terminal 5 decides on a subject on which information is required. The user then programs the terminal 5 with an identification of that subject, for example a sports team or a stock price, and frequency and optionally timing for which content relating to that subject is required. Optionally, the user specifies also the domains from which information is required to be sourced. The domains may be websites 53, 54, 55, specified by way of their URLs. The information programmed into the terminal 5 is transmitted by way of the duplex network 7 and the mobile operator server 13 to the agent 3, where the information is stored in the user preference database 60, the update frequency

database 62 and the content domain database 63 as appropriate. The information stored in these databases 60, 62, 63 is amendable by a user by the sending of appropriate amending information from the terminal 5.

5 When content relating to a chosen subject is due for updating, as indicated by the information stored in the update frequency database 62, the agent 3 conducts a search though the internet for information relating to that subject. The search is limited to those domains 53-55 specified by the user, if there are any. If the agent 3 discovers any content which has been updated for the subject since its last search, the last update
10 database 61 is marked with the time and date of the update, and the content is marked for delivery to the terminal 5. Content which has been sent to the terminal 5 previously is disregarded. Content which is marked for delivery and which the mobile operator server 13 determines is best transmitted using the DVB network 9, having regard to the user preferences, is sent to the broadcast operator 51 via the internet, where it is stored
15 whilst awaiting a broadcast request. If the mobile operator server 13 and the broadcast operator server 51 are the same, which could occur if they are run by a single operator, the last step can be omitted. Once the content has been sent to the broadcast operator server 51, the mobile operator server 13 signals to the terminal 5 that content is ready for broadcast, and includes a request for confirmation that the content is required. This step
20 may include an indication of the content, such as a document or program title and optionally a summary of the information contained. Once the terminal 5 signals that the user wants to receive the content, the mobile operator server 13 sends to the broadcast operator server 51 a broadcast request, which identifies the content and includes location information relating to the terminal, such as the cell in which the terminal is located. In
25 response, the broadcast operator server 51 loads the content from the cache 52 to the data carousel 45, from where it is broadcasted to the terminal 5.

To minimise power consumption in the terminal 5, it is provided with information identifying the broadcast time. This could be specified by the user or by the terminal 5,
30 and signalled to the broadcast operator server 51 via the mobile operator server 31. Alternatively, it is to be specified by the mobile operator server 13. Most likely, though, the broadcast time is specified by the broadcast operator server 51, and the time

information is signalled to the mobile operator server 51 for transmission to the terminal 5 over the duplex network 7.

5 The agent 3 may negotiate the transfer slot used to broadcast the content. For example, broadcasting content at night may be affordable to the user of the terminal 5 whereas broadcasting in the daytime might exceed the user's predefined cost limitations.

10 The agent 3a may serve as a group of users, for example supporters of a certain sports team. In this case, the information contained in the databases 60, 62, 63 may be specified by a designated terminal. The agent 3a, through the mobile 13, arranges for plural members of the group to expect content delivery over the DVB network 9 at a time specified by the broadcast operator server 51. The content remains in the data carousel 45 either until it has been successfully delivered to all members of the group, until the content is no longer relevant, for example because it has been updated, or until a timeout value has been exceeded.

15 Alternatively, the agent 3a may store user preferences for each of the users in the group. The user preferences relate to cost and delivery timing preferences. A first user, for example, may request content update at two hourly intervals between 9am and 11pm, and require delivery over a pay-network only if the content cannot be delivered free within 30 minutes of the update time and if the cost of delivery for a two-hour period does not exceed one Euro. A second user may request content update daily at 8pm, and not require delivery over a pay-network under any circumstances. Data indicative of these preferences is stored in the agent 3a.

25 The agent 3a also sources content relating to a subject in respect of which the users of the group are interested and to which the agent 3a is dedicated. Content is sourced from the Internet, by way of periodic searches.

30 Periodically, for example every five minutes, the agent 3a determines which of the users an item of content is destined for delivery to. This decision is made on the basis of the user preferences as regards update time and frequency. If a suitably large number of

users are deemed to require the content, then a slot for broadcast is negotiated with the DVB-T operator 51. Once the broadcast details are known, the agent 3a informs each of the relevant users of the broadcast details in any suitable manner over the network 7.

Each of the users in the group which received the broadcast then sends a confirmation
5 message to the agent 3a, which updates its database. Some users will not receive the broadcast, for example because they do not have a DVB-T receiver, because their device was switched-off and so on. The users which did not receive the broadcast are identified and listed. Those users whose user preferences would be met if the content were not delivered until the next broadcast (where details of the broadcast are known) are

10 identified, and removed from the list. In respect of each of the users remaining on the list, delivery is made, if possible, on a network selected according to the user's preferences and according to the networks to which the user has access or to which the user gains access. For those listed users which have repeatedly missed broadcasts and those for which it is known that reception from the DVB-T network 51 is not possible,

15 special considerations are made. In particular, the users are continually monitored to determine whether they have entered a 'hot-spot' over which content can be delivered without charge to the operator. Monitoring may involve periodic polling of the users, or requesting the users to report to the agent 3a when access to a hot-spot is possible. In this way, content delivery can be made via the hot-spot if one becomes available. Once
20 users are deemed to have received the content, the database is updated, and they are removed from the list. Delivery may be made via a GPPS or GSM network as the user preferences indicate that the end of an acceptable period for content delivery is imminent and if the user will tolerate the associated charges.

25 As an enhancement, each user in the group may set a relevance level of required content. For example, a user requiring content at a high relevance level may be caused to receive only content which is deemed to be very relevant to the subject. A user not having a high relevance level setting may be caused to receive the content which is very relevant as well as content which is less relevant. Relevance may be determined on the basis of a
30 computer classification, using a scheme similar to that used in Internet search engines for example.

It is not necessary that the terminal 5 be provided with user interface output devices suitable for delivering the content. For example, in an unshown embodiment, a PC (personal computer) may be connected to a wireless terminal via an infra-red, Bluetooth™ or a USB (universal serial bus) connection. In this example, the PC may be
5 used to control the terminal 5 to request information services, with broadcasts received by the terminal and forwarded to the PC for storage and/or immediate consumption. In this example, authentication of the mobile terminal on the duplex network 7 is required, which can be made by way of a SIM (subscriber identity module) or IMSI (international mobile subscriber identity).

Claims

1. A content delivery method comprising establishing a set of user preferences related to delivery of content; sourcing content in response to a request received from a terminal connected to a network and selecting based on said set of user preferences a network over which to deliver said content to said terminal.
2. A method as claimed in claim 1, comprising maintaining in an agent a log of sourced content relating to the request.
3. A method as claimed in claim 2, comprising maintaining in the log an indication of the delivery status of the content.
4. A method as claimed in any preceding claim, comprising acknowledging receipt of the content over a or the duplex network.
5. A method as claimed in claim 3 and claim 4, comprising updating the delivery status of the log on receiving an acknowledgement receipt.
6. A method as claimed in any preceding claim, comprising notifying over a duplex network the terminal prior to the delivery of content over a simplex network.
7. A method as claimed in any preceding claim, in which the user preferences relate to cost and/or delivery timing preferences.
8. A method as claimed in any preceding claim, comprising reviewing content items on a data carousel, and determining from the reviewing step if any forthcoming content matches the user request.
9. A method as claimed in any preceding claim, comprising conducting a search for content relating to the request, preferably using the internet.

10. A method as claimed in any preceding claim, comprising storing in a or the agent information relating to the last update of content relating to the request.
- 5 11. A method as claimed in any preceding claim, comprising storing in a or the agent information relating to the user's time and/or frequency of updating preferences.
12. A method as claimed in any preceding claim, comprising storing in a or the agent information relating to domains to which searching relating to the content request is limited.
- 10 13. A method as claimed in any preceding claim, comprising storing in an agent user preferences relating to plural users.
14. A method as claimed in claim 13, comprising sourcing an item of content, and
15 sending the content to plural users.
15. A method as claimed in claim 14, comprising maintaining in the agent a log of which users have received the item of content.
- 20 16. A method as claimed in any of claims 13 to 15, in which the plural users each are able to define a relevance level of content of which they require delivery.
17. A method as claimed in any of claims 13 to 16, comprising periodically sourcing content, and using the user preferences for the plural users to determine which users the
25 content is required by.
18. An agent connectable to a network, the agent being operable to establish a set of user preferences relating to delivery of content to a user terminal, to source content in response to a user request, and to deliver said content to a user terminal over a network
30 selected in dependence on said set of user preferences.
-

19. An agent as claimed in claim 18, arranged to maintain a log of sourced content relating to the request.

20. An agent as claimed in claim 19, arranged to maintain in the log an indication of the delivery status of the content.

21. An agent as claimed in any of claims 18 to 20, arranged to update the delivery status of the log on receiving an acknowledgement receipt.

22. An agent as claimed in any of claims 18 to 21, in which the user preferences relate to cost and/or delivery timing preferences.

23. An agent as claimed in any of claims 18 to 22, comprising means for reviewing content items on a data carousel, and means for determining from the reviewing step if any forthcoming content matches the user request.

24. An agent as claimed in any of claims 18 to 22, comprising means for searching for content relating to the request.

25. An agent as claimed in any of claims 18 to 24, comprising means for storing information relating to the last update of content relating to the request.

26. An agent as claimed in any of claims 18 to 25, comprising means for storing information relating to the user's time and/or frequency of updating preferences.

27. An agent as claimed in any of claims 18 to 25, comprising means for storing information relating to domains to which searching relating to the content request is limited.

28. An agent as claimed in any of claims 18 to 27, comprising means for storing user preferences relating to plural users.

29. An agent as claimed in claim 28, comprising means for sourcing an item of content, and for sending the content to plural users.

30. An agent as claimed in claim 29, comprising means for maintaining a log of which users have received the item of content.

31. An agent as claimed in any of claims 28 to 30, in which the agent is arranged to store for at least some of the plural users a relevance level of content of which delivery is required.

32. An agent as claimed in any of claims 28 to 31, comprising means for periodically sourcing content, and for using the user preferences for the plural users to determine which users the content is required by.

33. A content delivery system comprising a first duplex network, a second network and a user terminal connectable to said first and second networks, wherein the system further comprises an agent connectable to said first and second networks, the agent being operable to source content in response to a user request received from said user terminal via said first network, and to deliver said content to said terminal over a network selected in accordance with a set of user preferences.

34. A system as claimed in claim 33, in which the user preferences are established by the agent.

35. A system as claimed in claim 33, in which the user preferences are generated by the terminal.

36. A system as claimed in any of claims 33 to 35, in which the second network is a simplex network.

37. A system as claimed in claim 36, comprising means for notifying over the first network the terminal prior to the delivery of content over the second network.

38. A system as claimed in any of claims 33 to 35, in which the second network is a duplex network.

5 39. A system as claimed in any of claims 33 to 38, in which the agent is arranged to maintain a log of sourced content relating to the request.

40. A system as claimed in claim 39, in which the agent is arranged to maintain in the log an indication of the delivery status of the content.

10

41. A system as claimed in any of claims 33 to 40, in which the terminal is arranged to acknowledge receipt of the content over the duplex network or one of the duplex networks.

15 42. A system as claimed in claim 40 and claim 41, in which the agent is arranged to update the delivery status in the log on receiving an acknowledgement receipt.

43. A system as claimed in any of claims 33 to 42, in which the user preferences relate to cost and/or delivery timing preferences.

20

44. A system as claimed in any of claims 33 to 43, comprising means for reviewing content items on a data carousel, and means for determining from the reviewing step if any forthcoming content matches the user request.

25 45. A system as claimed in any of claims 33 to 44, comprising means for conducting a search for content relating to the request, preferably using the internet.

46. A system as claimed in any of claims 33 to 45, in which the agent is arranged to store information relating to the last update of content relating to the request.

30

47. A system as claimed in any of claims 33 to 46, in which the agent is arranged to store information relating to the user's time and/or frequency of updating preferences.

48. A system as claimed in any of claims 33 to 47, in which the agent is comprising storing in a or the agent information relating to domains to which searching relating to the content request is limited.

5

49. A system as claimed in any of claims 33 to 48, in which the agent comprises means for storing user preferences relating to plural users.

10

50. A system as claimed in claim 49, in which the agent comprises means for sourcing an item of content, and for sending the content to plural users.

51. A system as claimed in claim 50, comprising means for maintaining a log of which users have received the item of content.

15

52. A system as claimed in any of claims 49 to 51, in which the agent is arranged to store for at least some of the plural users a relevance level of content of which delivery is required.

20

53. A system as claimed in any of claims 49 to 52, in which the agent comprises means for periodically sourcing content, and for using the user preferences for the plural users to determine which users the content is required by

25

54. A content delivery method substantially as described with reference to any of the accompanying Figures.

55. An agent substantially as shown in and/or as described with reference to Figure 4 or Figure 8 of the accompanying drawings.

30

56. An system substantially as shown in and/or as described with reference to Figure 1a, Figure 1b or Figure 7 of the accompanying drawings.

Abstract

Hybrid Networks

5 A user through a mobile or fixed terminal 5 informs an agent 33 hosted by an operator server 13 of subjects in respect of which content is requested. The agent 33 searches the internet for relevant content, and determines from a set of user preferences, relating to cost and timing of delivery preferences, a network for use in delivering the content to the terminal. Delivery may be made by a free network, e.g. a WLAN or Bluetooth network,
10 if one is available, or over an expensive network such as a 3G, GSM or GPRS network if the content is required quickly. If delivery is to be made over a broadcast network 11, such as a DVB-T network 11, a signal is sent to the terminal over a mobile telephone network 7 giving the time of broadcast, in response to which the terminal 5 enables its broadcast receiver at the appropriate time. Also, the agent 33 periodically reviews the
15 content on a data carousel 45 which is awaiting broadcast, and informs the terminal 5 of any forthcoming content which is relevant to the user request.

Figure 1a




Figure 1




Figure 2




Figure 2




Figure 3




Figure 4




Figure 5a




Figure 5b




Figure 6




Figure 7




Figure 8

PCT Application
PCT/EP2003/050784



**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.